

Structural Performance Ratings* (AAMA Certified)

Please Note: For the most recent version of this document go to www.cascadewindows.com/products.

	Operation	Test Size	Air Infiltration (cfm/sqft)	Water Resistance Test Pressure (psf)	Structural Rating
WinPro Series					
Picture	Fixed-O	79" X 79"	< .01	14.6	F-C40
Slider	XO	72" X 60"	.08	5.4	HS-C35
Slider	XOX	120" X 60"	.08	4.6	HS-LC30
Single Hung	H	48" X 72"	.12	5.25	LC-PG35
Sliding Glass Door	SGD-XO	72" X 82"	.15	4.5	LC-PG35
Empire Series					
Picture	Fixed-O	79" X 79"	< .01	14.6	F-C40
Slider	XO	72" X 60"	.08	5.4	HS-C35
Slider	XOX	120" X 60"	.08	4.6	HS-C30
Single Hung	H	48" X 72"	.06	5.25	LC-PG35
Cascade Series					
Picture	Fixed-O	96" X 79"	< .01	12.12	LC-PG30
Slider	XO	72" X 60"	.08	5.4	HS-C35
Slider	XOX	120" X 72"	.11	3.76	HS-LC25
Single Hung	H	48" X 72"	.06	5.25	LC-PG35
Casement	X	36" X 60"	.01	12.0	LC-PG50
Awning	X	48" X 32"	< .01	6.0	LC-PG40
Sliding Glass Door	SGD-XO	72" X 82"	.15	4.5	LC-PG35
ThermalPro Series					
Picture	Fixed-O	79" X 79"	< .01	14.6	F-C40
Slider	XO	72" X 60"	.08	5.4	HS-C35
Slider	XOX	120" X 60"	.08	4.6	HS-C30
Single Hung	H	48" X 96"	.06	5.25	LC-PG35
LbL 8000 Series					
Tilt Double Hung	TDH	48" X 77"	.19	3.75	LC-PG25
Picture	Fixed-O	108" X 72"	.02	12	LC-PG30
Slider	XXX	120" X 60"	.09	3.75	LC-PG25

Revised 1/24/2012

* Data shown on this sheet is subject to change based on test dates and certification cycles. Data is based on results from certified tests and/or simulations performed by accredited independent laboratories on products manufactured by Cascade Windows. Actual product performance may vary.

