

Dealer Name: _____ Account# _____ Date: _____

Submitted by: _____ Phone: _____ Email: _____

Builder, Lot# & Sub Division: _____

Street Address: _____

City: _____ State _____ Zip Code _____ P.O.# _____

Check here if jobsite delivery \$125.00 delivery fee if delivering to a jobsite, not available in all areas.


Jobsite Contact: _____ Phone: _____

CHECK PANEL OPERATION BELOW & INDICATE NET SIZE

Net Size of Window (Width x Height)	Jamb Depth
	5 1/4"


Folding window uses the 2750 sash on all options excluding if Black Laminate is chosen as frame color. (Blk/Blk is not available on 2750 sash).

2.0.2 Outswing




Exterior panels not to scale

2.2.0 Outswing




3.0.3 Outswing




Exterior panels not to scale

3.3.0 Outswing



3.1.2 Outswing




Exterior panels not to scale

3.2.1 Outswing




4.0.4 Outswing




Exterior panels not to scale

4.4.0 Outswing




4.1.3P Outswing




Exterior panels not to scale


4.3P.1 Outswing



4.2.2 Outswing




4.1P.3 Outswing



Exterior panels not to scale

4.3.1P Outswing



Int/Ext Color:	White	Beige	Black	Handle Style:	Straight (standard)	Flared (optional)	
Exterior over White:	Terra Tone	Bronze	Black-Matte	Handle Color:	White	Brushed Chrome	Black
Frame Style:	Block	1" Fin	1 3/8" Fin	Bolt Color:	White	Brushed Chrome	Black
Sill Color:	Clear Anodized	Bronze Anodized		Release Lever:	Brushed Stainless	Bronze Powder Coat	
Sill Type:	Standard	ADA*		Glass:	EC+/Clear	Other	_____

NOTE: Regardless of sill type, the foundation must support the sill height variance requirement of 1/16" maximum across the entire sill length. In conjunction with the sill, the framing of the rough opening must be installed plumb, square, and true within 3/16". The header must be flat and designed to uphold the deflection requirement of not more than 1/8" over the entire length of the unsupported span when fully loaded. Side jambs and pocket framing must be constructed of a continuous flat solid surface that is plumb. The folding door and window system require an additional structural load calculation for the header, equal or greater than 7 pounds per square foot of rough opening, with same deflection criteria above.

Additional charges may apply: Jobsite delivery is not available in all areas. Warranty is subject to following the provided installation instructions and using an adequate header for support. Cascade Windows does not warrant the installation of the product, or adjustment related requests.

Dealer Name: _____ Account# _____ Date: _____

Submitted by: _____ Phone: _____ Email: _____

Builder, Lot# & Sub Division: _____

Street Address: _____

City: _____ State _____ Zip Code _____ P.O.# _____

Check here if jobsite delivery \$125.00 delivery fee if delivering to a jobsite, not available in all areas.


Jobsite Contact: _____ Phone: _____

CHECK PANEL OPERATION BELOW & INDICATE NET SIZE

Net Size of Window (Width x Height)	Jamb Depth
	5 1/4"


Folding window uses the 2750 sash on all options excluding if Black Laminate is chosen as frame color. (Blk/Blk is not available on 2750 sash).

5.0.5 Outswing




Exterior panels not to scale

5.5.0 Outswing




5.1.4 Outswing




Exterior panels not to scale

5.4.1 Outswing




5.2.3 Outswing



Exterior panels not to scale

5.3.2 Outswing



Int/Ext Color:	White	Beige	Black	Handle Style:	Straight (standard)	Flared (optional)
Exterior over White:	Terra Tone	Bronze	Black-Matte	Handle Color:	White	Brushed Chrome Black
Frame Style:	Block	1" Fin	1 3/8" Fin	Bolt Color:	White	Brushed Chrome Black
Sill Color:	Clear Anodized	Bronze Anodized		Release Lever:	Brushed Stainless	Bronze Powder Coat
Sill Type:	Standard	ADA*		Glass:	EC+/Clear	Other _____

Additional charges may apply: Jobsite delivery is not available in all areas. Warranty is subject to following the provided installation instructions and using an adequate header for support. Cascade Windows does not warrant the installation of the product, or adjustment related requests.

NOTE: Regardless of sill type, the foundation must support the sill height variance requirement of 1/16" maximum across the entire sill length. In conjunction with the sill, the framing of the rough opening must be installed plumb, square, and true within 3/16". The header must be flat and designed to uphold the deflection requirement of not more than 1/8" over the entire length of the unsupported span when fully loaded. Side jambs and pocket framing must be constructed of a continuous flat solid surface that is plumb. The folding door and window system require an additional structural load calculation for the header, equal or greater than 7 pounds per square foot of rough opening, with same deflection criteria above.

Dealer Name: _____ Account# _____ Date: _____

Submitted by: _____ Phone: _____ Email: _____

Builder, Lot# & Sub Division: _____

Street Address: _____

City: _____ State _____ Zip Code _____ P.O.# _____

Check here if jobsite delivery \$125.00 delivery fee if delivering to a jobsite, not available in all areas.


Jobsite Contact: _____ Phone: _____

CHECK PANEL OPERATION BELOW & INDICATE NET SIZE

Net Size of Window (Width x Height)	Jamb Depth
	5 1/4"


Folding window uses the 2750 sash on all options excluding if Black Laminate is chosen as frame color. (Blk/Blk is not available on 2750 sash).

6.0.6 Outswing




Exterior panels not to scale

6.6.0 Outswing




6.1.5P Outswing




Exterior panels not to scale

6.5P.1 Outswing




6.1P.5 Outswing




Exterior panels not to scale

6.5.1P Outswing




6.2.4 Outswing



Exterior panels not to scale

6.4.2 Outswing




6.3P.3 Outswing



Exterior panels not to scale

6.3.3P Outswing



Int/Ext Color:	White	Beige	Black
Exterior over White:	Terra Tone	Bronze	Black-Matte
Frame Style:	Block	1" Fin	1 3/8" Fin
Sill Color:	Clear Anodized	Bronze Anodized	
Sill Type:	Standard	ADA*	

Handle Style:	Straight (standard)	Flared (optional)	
Handle Color:	White	Brushed Chrome	Black
Bolt Color:	White	Brushed Chrome	Black
Release Lever:	Brushed Stainless	Bronze Powder Coat	
Glass:	EC+/Clear	Other _____	

Additional charges may apply: Jobsite delivery is not available in all areas. Warranty is subject to following the provided installation instructions and using an adequate header for support. Cascade Windows does not warrant the installation of the product, or adjustment related requests.

NOTE: Regardless of sill type, the foundation must support the sill height variance requirement of 1/16" maximum across the entire sill length. In conjunction with the sill, the framing of the rough opening must be installed plumb, square, and true within 3/16". The header must be flat and designed to uphold the deflection requirement of not more than 1/8" over the entire length of the unsupported span when fully loaded. Side jambs and pocket framing must be constructed of a continuous flat solid surface that is plumb. The folding door and window system require an additional structural load calculation for the header, equal or greater than 7 pounds per square foot of rough opening, with same deflection criteria above.